

Manufacturer Certificated





CERT. No.: 282Q19070712006

CERT. No.: 282E19070712007

Product Specification

Model: TTX215BVT-02

21.5"TFT Display Module (1080*1920)

This module uses RoHS material

Tailor Pixels Technology Co., Ltd. www.tailorpixels.com tailor@tailorpixels.com Ph: 86-755-8821 2653

Contents in this document are subject to change without notice. No part of this document can be reproduced or transmitted by any means for any purpose without the written permission of Tailor Pixels Technology Co., Ltd.

PRODUCT GROUP		REV	เรรเ	JE DATE	ר <u> </u>	ailorpixels	
	TFT- LCD P	RODUCT	A0	202	1-10-14	A .	Professional Manufacturer of Display
SPEC. NUMBER SPEC . TITLE						•	PAGE
TTX215BVT-02 Product Specification					ition		2 OF 26
		REVISIO	ON HISTO	ORY			
REV.	ECN No.	DESCRIPTION	OF CHANGES		DATE		PREPARED
A0		Initial R	elease		2021-10-1	14	

PROI	DUCT	r group	REV	ISSUE DATE		
TFT-	TFT- LCD PRODUCT			2021-10-14	A P	rofessional Manufacturer of Display
SPEC. NUM	BER		SPEC. TITLE			PAGE
		TTX215BVT-	02 Product S	pecification		3 OF 26
		Co	ntents			
No.			ltems			Page
	REVIS	SION HISTORY				2
	CONT	TENTS				3
1.0	Gener	al Description				4
2.0	2.0 Absolute Maximum ratings					6
3.0	3.0 Electrical specifications.					7
4.0	Optica	al specifications.				9
5.0	Interfa	ace Connection				14
6.0	Signa	l Timing Specificatio	n			16
7.0	Input	Signals, Display Colo	ors & Gray Sca	le of Colors		18
8.0	LVDS	VESA Data Mapping				19
9.0	Power	r Sequence				20
10.0	Mech	anical Characteristics	5			21
11.0	Reliab	oility Test				22
12.0	Handl	ing & Cautions.				22
13.0	Label					23
14.0	14.0 Packing information					24
15.0	Mech	anical Outline Dimer	nsion			25

PRODUCT	r group	REV	ISSUE DATE		ailorpixels
TFT- LCD PRODUCT		A0	2021-10-14	A P	rofessional Manufacturer of Display
SPEC. NUMBER	SPEC. TITLE				PAGE
	TTX215BVT-02 Product Specification				4 OF 26

1.0 GENERAL DESCRIPTION

1.1 Introduction

TTX215BVT-02 is a color active matrix TFT LCD FOB using amorphous silicon TFT's(Thin Film Transistors) as an active switching devices. This module has a 21.5 inch diagonally measured active area with FHD resolutions (1080 horizontal by 1920 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical Stripe and this module can display 16.7M colors. The TFT-LCD panel used for this module is a low reflection and higher color type. The LED Driver for back-light driving is built in this model.

All input signals are LVDS interface compatible.



1.2 Features

- LVDS Interface Support MIPI & Edp Interface in Qctober 2021
- High-speed response
- Real 8 bit color depth , display 16.7M colors
- DE (Data Enable) only
- Wide Temperature Range -20°C-70°C Operation Test
- Built In Self Test(BIST) Function
- Low driving voltage and low power consumption
- Normal Reverse type, Forward Type by choose

PRODUCT GROUP		REV	ISSUE DATE		ailorpixels
TFT- LCD PRODUCT		A0	2021-10-14	АР	rofessional Manufacturer of Display
SPEC. NUMBER SPEC. TITLE					PAGE
TTX215BVT-02 Product Specification					5 OF 26
1.3 Application	1.3 Application				
• White Goods					
1.4 General Specification The followings are general specifications at the QV215FHB-N11(FOB).					

<Table 1. General Specifications>

Parameter	Specification	Unit	Remarks
Active Area	260.28(H)*478.656(V)	mm	
Number Of Pixels	1080(H)×1920(V)	pixels	
Pixel Pitch	80.33/80.33/80.34*249.3	um	
Pixel Arrangement	Pixels RGB stripe arrangement		
Display Mode	Normally Black		
Display Colors	16.7M	colors	
Luminance of LCM	600	nit	
Surface Treatment	AG25		
Contrast Ratio	1000:1(typ.)		
Viewing Angle(CR>10)	85/85/85/85(typ.)		
Response Time	30(typ.)	ms	
Color Gamut	72%NTSC		
Operation temperature	-20~70	°C	
Storage temperature	-30~80	°C	
Panel outline	267.28*489.956	mm	

PRODUCT GROUP		REV	ISSUE DATE	Т	ailorpixels
TFT- LCD PRODUCT		A0 2021-10-14		A	Professional Manufacturer of Display
SPEC. NUMBER	SPEC. TITLE				PAGE
	TTX215BVT-02 Product Specification				6 OF 26

2.0 ABSOLUTE MAXIMUM RATINGS

The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit.

< Table 2. Absolute Maximum Ratings>

Parameter		Symbol	Min.	Max.	Unit	Remarks
Power Supply	LCD Module	VDD	VSS-0.3	5.5	V	Ta = 25 °C Note 1&2
Operating Temperature		Т _{ор}	-20	+70	°C	
Storage Temperature		T _{ST}	-30	+80	°C	
Operating Ambient Humidity		Нор	10	80	%RH	Note 3
Storage H	umidity	Hst	10	80	%RH	

Note:

- 1. These range above is maximum value not the actual operating temperature . Actual Operating temperature is no more than 40° C and temperature refers to the LCM surface temperature ; Length of operation: No more than <u>8</u> hours per day, and no more than <u>4</u> hours of continuous use one time.
- 2. BOE is not responsible for product problems beyond the use conditions.
- 3. Temperature and relative humidity range are shown in the figure below. Wet bulb temperature should be 39 °C max. and no condensation of water.



PRODUCT	GROUP	REV	ISSUE DATE	-10	ailorpixels
TFT- LCD PRODUCT		A0	2021-10-14	A F	rofessional Manufacturer of Display
SPEC. NUMBER	SPEC. TITLE				PAGE
TTX215BVT-02 Product Specification					7 OF 26
		_			

3.0 ELECTRICAL SPECIFICATIONS

3.1 TFT LCD Module

< Table 3. LCD Module Electrical specifications > [Ta=25±2 °C]

Parameter		Min.	Тур.	Max.	Unit	Remarks
Power Supply Voltage	V _{DD}	4.5	5	5.5	V	Note 1
Permissible Input Ripple Voltage	V _{RF}	-	-	100	mV	At V _{DD} = 3.3V
Power Supply Current	I _{DD}	-	300	680	mA	Note 1
High Level Differential Input Threshold Voltage	V _{IH}	-	-	+100	mV	
Low Level Differential Input Threshold Voltage	V _{IL}	-100	-	-	mV	
Differential input voltage	I V _{ID} I	0.2	0.4	0.6	V	
Differential input common mode voltage	Vcm	0.6	1.2	2.2	V	
	P _D	-	1.5	-	W	Note 1
Power Consumption	-	-	-	-	W	
	P _{total}	-	-	-	W	

Notes : 1. The supply voltage is measured and specified at the interface connector of FOB. The current draw and power consumption specified is for 3.3V at 25°C.

a) Typ : Mosaic Pattern

Max: R G B Pattern

PRODUCT	GROUP	REV	ISSUE DATE	_r	ailorpixels
TFT- LCD PRODUCT		A0	2021-10-14	A	Professional Manufacturer of Display
SPEC. NUMBER	SPEC. TITLE				PAGE
	TTX215BVT-	02 Product S	pecification		8 OF 26
					•

3.2 Backlight Uint

Parameter		Min.	Тур.	Max.	Unit	Remarks
LED Light Bar Input Voltage Per Input Pin	VPIN	47.6	51	54.4	V	Duty 100%
LED Light Bar Input Current Per Input Pin	IPIN	-	60	-	mA	Note1,2
LED Power Consumption	P_{BL}	22.84	24.48	26.12	W	Note 3
LED Life-Time	-	30,000	-		Hrs	Note 4

╸╫╗╄╗╄╗┡╗┡╗╊╗╄╦╄╦╄╦╄╦╄╦╊╦╊╦╊╦ ╸╫╗╄╗╊╗┠╗╊╗╊╦╊╦╊╦╊╦╊╦╊╦╊╦╊╦╊╦╊╦ ╸╫╗╄╦╊╗╊╗╊╦╊╦╊╦╊╦╊╦╊╦╊╦╊╦

╸╫╗╫╗╫╗╟╗╟╗╟╗┠╗┠╗┠╗┠╗┠╗┠╗┠╗ ╺╫╗╫╗╫╗┠╗┠╗┠╗┠╗┠╗┠╗┠╗┠╗┠╗┠╗ ╺╫╗╫╗╫╗┠╗┠╗┠╗┠╗┠╗┠╗┠╗┠╗┠╗┠╗ ╺╫╗╄╗╄╗┠╗┠╗┠╗┠╗┠╗┠╗┠╗┠╗ LED: 17*4*2=136 PCS

LED bar consists of 136LED packages,4strings(parallel)*17packages(serial)*2

Note1: There are one light bar ,and the specified current is input LED chip 100% duty current

Note2: The sense current of each input pin is 60mA

Note3: PBL=2*4Input pins*VPIN \times IPIN

Note4: The lifetime is determined as the time at which luminance of LED become 50% of the initial brightness or not normal lighting at IPIN=70mA on condition of continuous operating at $25 \pm 2 \degree$ C

PRODUCT GROUP		REV	ISSUE DATE	Ţ	ailorpixels	
TFT- LCD PRODUCT		A0	2021-10-14	A), Professional Manufacturer of Display	
SPEC. NUMBER	SPEC. TITLE				PAGE	
	TTX215BVT-		9 OF 26			

4.0 OPTICAL SPECIFICATION

4.1 Overview

The test of Optical specifications shall be measured in a dark room (ambient luminance ≤ 1 lux and temperature = $25\pm2^{\circ}$ C) with the equipment of Luminance meter system (Goniometer system and TOPCON BM-5) and test unit shall be located at an approximate distance 50cm from the LCD surface at a viewing angle of θ and Φ equal to 0°. We refer to $\theta \emptyset = 0$ (=03) as the 3 o'clock direction (the "right"), $\theta Ø = 90$ (= $\theta 12$) as the 12 o'clock direction ("upward"), $\theta \emptyset = 180 (= \theta 9)$ as the 9 o'clock direction ("left") and $\theta \emptyset = 270 (= \theta 6)$ as the 6 o'clock direction ("bottom"). While scanning θ and/or \emptyset , the center of the measuring spot on the Display surface shall stay fixed. The backlight should be operating for 30 minutes prior to measurement. VDD shall be 3.3+/- 0.3V at 25°C. Optimum viewing angle direction is 6 'clock.

4.2 Optical S	4.2 Optical Specifications <table 4.="" optical="" specifications=""></table>								
Paramo	eter	Symbol	Condition	Min.	Тур.	Max.	Unit	Remark	
	Horizontol	Θ ₃		-	85	-	Deg.		
Viewing Angle	TIONZONIAI	Θ ₉	CR > 10	-	85	-	Deg.	Note 1	
range	Vertical	Θ ₁₂		-	85	-	Deg.		
	ventical	Θ ₆		-	85	-	Deg.		
Luminance Co	ntrast ratio	CR	⊖ = 0°	900	1000	-	-		
Transmit	tance	Tr	0-0	3.5	3.9	-	% nit 3 -	FOB	
Luminance of White	5 Points	Y _w	Θ = 0°	500	600	-	nit		
White Chro	moticity	X _w	$\Theta = 0^{\circ}$	0.283	0.313	0.343	-		
white Child	Пацску	y _w	0-0	0.299	0.329	0.359	-		
	Red	x _R			0.649		-		
	Iteu	У _R			0.346		- - - - -		
Reproduction	Green	x _G	$\Theta = 0^{\circ}$	0.03	0.329	TO 03	-		
of color	Oreen	У _G	0 - 0	-0.03	0.623	+0.03	-		
	Blue	x _B			0.151		-		
	Dide	У _В			0.064		-		
Gamı	ut	-	-	68	72	-	%		
Response (Rising + F	e Time Falling)	T _{RT}	Ta= 25° C Θ = 0°	-	30	35	Ms	Note 6	
Cross T	ſalk	СТ	$\Theta = 0^{\circ}$	-	-	2	%		

PRODUCT GROUP		KEV	ISSUE DATE		ailorpixels
TFT- LCD PROI	DUCT	A0	2021-10-14	A Pr	ofessional Manufacturer of Display
SPEC. NUMBER	·	SPEC. TITLE			PAGE
	TTX215BVT-0	02 Product Sp	pecification		10 OF 26

Notes :

1. Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing angles are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface (see FIGURE 1).

2. Contrast measurements shall be made at viewing angle of Θ = 0 and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state .

(see FIGURE 1) Luminance Contrast Ratio (CR) is defined mathematically.

3. Center Luminance of white is defined as luminance values of 5 point average across the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display.

4. The White luminance uniformity on LCD surface is then expressed as : Δ Y =Minimum Luminance of 5(or 13) points / Maximum Luminance of 5(or 13) points. (see FIGURE 2 and FIGURE 3).

5. The color chromaticity coordinates specified in Table 5 shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel.

6. The electro-optical response time measurements shall be made as FIGURE 4 by switching the "data" input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is Tr, and 90% to 10% is Td.

7. Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (YA) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (YB) of that same area when any adjacent area is driven dark. (See FIGURE 5).





Center Luminance of white is defined as luminance values of center 5 points across the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display.







The White luminance uniformity on LCD surface is then expressed as : Δ Y5 = Minimum Luminance of five points / Maximum Luminance of five points (see FIGURE 2), Δ Y13 = Minimum Luminance of 13 points /Maximum Luminance of 13 points (see FIGURE 3).





The electro-optical response time measurements shall be made as shown in FIGURE 4 by switching the "data" input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is Td and 90% to 10% is Tr.



The location measured will be exactly the same in both patterns

Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (YA) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (YB) of that same area when any adjacent area is driven dark (Refer to FIGURE 5).

				1
PRODUCT	GROUP	REV	ISSUE DATE	Tailorpixels
TFT- LCD PI	RODUCT	A0	2021-10-14	A Professional Manufacturer of Display
SPEC. NUMBER		SPEC. TITLE		PAGE
	TTX215BVT	-02 Product Sp	ecification	14 OF 26
5.0 INTERFAC 5.1 LED Ligh	E CONNECTION.			
LED Connec				

PRODUCT GROUP		REV	ISSUE DATE		ailorpixels
TFT- LCD PI	RODUCT	A0	2021-10-14	A Pi	rofessional Manufacturer of Display
SPEC. NUMBER		SPEC. TITLE			PAGE
	TTX215BVT-	02 Product Sp	ecification		15 OF 26

5.0 INTERFACE CONNECTION. 5.2 LVDS Interface Connection

The electronics interface connector is UJU IS100-L30R-C23or Equivalent.

< Table 5. FOB Pinmap >

Terminal	Symbol	Functions
Pin No.	Symbol	Description
1	RXO0-	Negative Transmission data of Pixel 0 (ODD)
2	RXO0+	Positive Transmission data of Pixel 0 (ODD)
3	RXO1-	Negative Transmission data of Pixel 1 (ODD)
4	RXO1+	Positive Transmission data of Pixel 1 (ODD)
5	RXO2-	Negative Transmission data of Pixel 2 (ODD)
6	RXO2+	Positive Transmission data of Pixel 2 (ODD)
7	STBYB(NC)	*Reserved for LCD manufacturer's use (No Connection)
8	RXOC-	Negative Transmission Clock (ODD)
9	RXOC+	Positive Transmission Clock (ODD)
10	RXO3-	Negative Transmission data of Pixel 3 (ODD)
11	RXO3+	Positive Transmission data of Pixel 3 (ODD)
12	RXE0-	Negative Transmission data of Pixel 0 (EVEN)
13	RXE0+	Positive Transmission data of Pixel 0 (EVEN)
14	GND	Power Ground
15	RXE1-	Negative Transmission data of Pixel 1 (EVEN)
16	RXE1+	Positive Transmission data of Pixel 1 (EVEN)
17	GND	Power Ground
18	RXE2-	Negative Transmission data of Pixel 2 (EVEN)
19	RXE2+	Positive Transmission data of Pixel 2 (EVEN)
20	RXEC-	Negative Transmission Clock (EVEN)
21	RXEC+	Positive Transmission Clock (EVEN)
22	RXE3-	Negative Transmission data of Pixel 3 (EVEN)
23	RXE3+	Positive Transmission data of Pixel 3 (EVEN)
24	GND	Power Ground
25	CTL	*Reserved for LCD manufacturer's use (CTL_DVR)
26	CE	*Reserved for LCD manufacturer's use (CE_DVR)
27	NC	No Connection
28	VDD	
29	VDD	Power Supply: +5V(4.5V~5.5V)
30	VDD	

PRODUCT GROUP		REV	ISSUE DATE		ailorpixels
TFT- LCD P	RODUCT	A0	2021-10-14	A Pr	ofessional Manufacturer of Display
SPEC. NUMBER		SPEC. TITLE			PAGE
	TTX215BVT-	02 Product Sp	ecification		16 OF 26

6.0 SIGNAL TIMING SPECIFICATION

6.1 The QV215FHB-N11 is operated by the DE only.

lte	em	Symbols	Min	Тур	Мах	Unit
Frequ	uency	1/Tc		61.86		MHz
	Frame Rate	F	58	60	62	Hz
Unvizontal	Total	Т _Н	580	580	594	Т _Н
Horizontai	Display	T _{HD}		540	Т _Н	
	Blank	Т _{нв}	40	40	54	Т _н
	Total	T _V	1950	1950	2112	Т _{СLК}
Vertical	Display	T _{VD}		1920		Т _{СLК}
	Blank	T _{VB}	30	30	192	Т _{СLК}

< Table 6. FOB Timing Spec >

	PRODUCT	GROU	Р	RI	EV	ISSUE DA	ATE		ailorp	ixels
	TFT- LCD PRODUCT				A0 2021-10-14			A Pro	ofessional Manufactur	rer of Display
SPE	C. NUMBER			SPEC	. TITLE				PAG	GE
0		тт		T 02 Dro	duct Sp	ocification			17 (75 26
		11	X213BV	1-02 PIO	auci spe	ecilication			17 0	JF 20
6.2 LVDS Rx Interface Timing Parameter										
	<	Table 7. LV	/DS Rx	Interfac	e Timin	a Specifica	tion>			
						Bating				
	Item		Signal	Symbol	Min	Tvp	Ma	ax	Unit	
	Clock Frequency			ByECLK	20	-	1(20	MHz	
	Clock Period		CLK	Bytcik	10	-	5	0	ns	-
	1 data bit time			UI	-	1/7		-	Byterk	-
	Clock high time			Тіусн		4			UI	-
	Clock low time		CLK			3			UI	-
	Position 1			TPOSt	-0.25	0	0.	25		-
	Position 2				0.75	-	1.	25		
	Position 3			T _{POS3}	0.75	1	1.5	25		
	Position 4			T _{POS4}	1.75		2.	25		
	Position 5			T _{POS5}	1.75	2	2.	25		
	Position 6			T _{POS6}	2.75	-	3.	25		
	Position 7			T _{POS7}	2.75	3	3.	25		
	Position 8		DATA	T _{POS8}	3.75	-	4.	25	UI	
	Position 9			T _{POS9}	3.75	4	4.	25		
	Position 10			T _{POS10}	4.75	-	5.	25		
	Position 11			T _{POS11}	4.75	5	5.	25		
	Position 12			T _{POS12}	5.75	-	6.	25		
	Position 13		1	T _{POS13}	5.75	6	6.	25		
	Position 14			T _{POS14}	6.75	-	7.	25		
	PLL wake-up time			TenPLL	-		15	50	us	1
	CI KP - CI KN	Τυ	исн	R _{xTCLK} = 1 / R _{xF}	CLK	TLVCL		0V		_







PRODUCT GROUP		REV	ISSUE DATE	Ţ	ailorpixels
TFT- LCD PF	RODUCT	A0	2021-10-14	A F	Professional Manufacturer of Display
SPEC. NUMBER		SPEC. TITLE			PAGE
	TTX215BVT-	TTX215BVT-02 Product Specification		20 OF 26	

9.0 POWER SEQUENCE

To prevent a latch-up or DC operation of the LCD module, the power on/off seq uence shall be as shown in below

Devemator		Units		
Farameter	Min	Тур	Max	Units
T1	0.5	-	10	ms
T2	10	-	60	ms
T4	200	-	-	ms
T5	200	-	-	ms
Τ7	0	-	50	ms
T8	0.5	-	20	ms
Т9	1000	-	-	ms
_	_	_	-	ms
_	-	_	_	ms

PRODUCT	GROUP	REV	ISSUE DATE	Т	ailorpixels			
TFT- LCD PRODUCT		A0	2021-10-14	A Professional Manufacturer of				
SPEC. NUMBER		SPEC. TITLE			<i>P</i> AGE			
	TTX215BVT-	21 OF 26						
10.0 MECHANICA								
10.1 Dimensiona	10.1 Dimensional Requirements							
FIGURE 6 shows Other parameters	mechanical outlines for are shown in Table 8.	or the model Q	/215FHB-N11.					

<Table 8. Dimensional Parameters>

Parameter	Specification	Unit
Active Area	260.28(H)*478.656(V)	mm
Number of pixels	1080 (H) x 1920 (V)	
Pixel pitch	0.1335(H)×0.1335(V)	mm
Pixel arrangement	RGB Vertical stripe	
Display colors	16.7M	
Display mode	Normally Black	
Dimensional outline	292.2 (H)*495.6(V) *8.0(D)typ	mm
Weight	-	gram

10.2 Mounting

See FIGURE 6.

10.3 AG and Polarizer Hardness.

The surface of the LCD has a Anti Glare coating to minimize reflection and a coating to reduce scratching.

10.4 Light Leakage

Light Leakage shall be checked by naked eye Applying Limit sample and/or 10% ND filter with conditions as follow:

1. With a viewing distance of 500mm from the screen.

2.With overhead light less than 350lux

3. Viewing angle Within 45 degrees at Left/Right/Upper/Lower.

4. Check pattern with Black, White and 32-gray (Half-gray) screens.

PRODUCT GROUP			REV	ISSUE DATE	Tailorpixels			
TFT- LCD PRODUCT			A0	2021-10-14	A Professional Manufacturer of Display			
SPEC. NUMBER			SPEC. TITLE		PAGE			
		TTX215BVT-02 Product Specification			22 OF 26			
11.0 RELIABILITY TEST The Reliability test items and its conditions are shown in below. <table 9.="" reliability="" test=""></table>								
No		Test Items	Conditions	Conditions				
1	High temp	erature storage test	Ta = 80 °C,	Ta = 80 °C, 72 hrs				
2	Low temperature storage test		Ta = -30 °C	Ta = -30 °C, 72 hrs				
3	High temperature & high humidity (operation test)		^y Ta = 50 °C,	Ta = 50 °C, 80%RH, 72 hrs				
4	High temperature operation test		Ta = 70 °C,	Ta = 70 °C, 72 hrs				
5	Low temperature operation test		Ta = -20 °C	Ta = -20 °C, 72 hrs				
6	Thermal shock		Ta = -20 °C	Ta = -20 ℃ ↔ 60 ℃ (1 hr), 100 cycle				
7	Drop (non-operating)		60cm/1 cor	60cm/1 corner/3 edges/6 faces				
8	Shock test (non-opera	iting)	220G, Half ±X,±Y,±2	220G, Half Sine Wave 2msec $\pm X, \pm Y, \pm Z$ Once for each direction				
9	Electro-sta (non-opera	tic discharge test ting)	Air : 1 Contact :	Air : 150 pF, 330Ω, 15 KV Contact : 150 pF, 330Ω, 8 KV				

12.0 HANDLING & CAUTIONS

- (1) Cautions when taking out the module
- Pick the pouch only, when taking out module from a shipping package.
- (2) Cautions for handling the module
 - As the electrostatic discharges may break the LCD module, handle the LCD module with care. Peel a protection sheet off from the LCD panel surface as slowly as possible.
 - As the LCD panel and back light element are made from fragile glass material, impulse and pressure to the LCD module should be avoided.
 - As the surface of the polarizer is very soft and easily scratched, use a soft dry cloth without chemicals for cleaning.
 - Do not pull the interface connector in or out while the LCD module is operating.
 - Put the module display side down on a flat horizontal plane.
 - Handle connectors and cables with care.
- (3) Cautions for the operation
 - When the module is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the LCD panel would be damaged.
 - Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.

PRODUCT	GROUP	REV	ISSUE DATE	Tailorpixels	
TFT- LCD PI	RODUCT	A0	2021-10-14		
SPEC. NUMBER	SPEC. TITLE				PAGE
	TTX215BVT-02 Product Specification				23 OF 26

- (4) Cautions for the atmosphere
 - Dew drop atmosphere should be avoided.
 - Do not store and/or operate the LCD module in a high temperature and/or humidity atmosphere. Storage in an electro-conductive polymer packing pouch and under relatively low temperature atmosphere is recommended.
- (5) Cautions for the module characteristics
 - Do not apply fixed pattern data signal to the LCD module at product aging.
 - Applying fixed pattern for a long time may cause image sticking.
- (6) Other cautions
 - Do not disassemble and/or re-assemble LCD module.
 - Do not re-adjust variable resistor or switch etc.
 - When returning the module for repair or etc., Please pack the module not to be broken. We recommend to use the original shipping packages.

13.0 LABEL

TBD

PRODUCT	GROUP	REV	ISSUE DATE	Tailorpixels	
TFT- LCD PI	RODUCT	A0	2021-10-14	A Professional Manufacturer of Display	
SPEC. NUMBER	SPEC. TITLE				PAGE
	TTX215BVT-02 Product Specification				24 OF 26

14.0 PACKING INFORMATION

TBD

